

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME I LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
520	<i>Chatham Beach Lighted Whistle Buoy C</i>	41 39 12 N 69 55 30 W	Mo (A) W		5	Red and white stripes with red spherical topmark.	
	*						3/04
*19676	Billington Cove Marina Channel Buoy 1	41 25 07 N 71 30 08 W				Green can.	Private aid.
							3/04
*19677	Billington Cove Marina Channel Buoy 2	41 25 07 N 70 30 08 W				Red nun.	Private aid.
							3/04
*19678	Billington Cove Marina Channel Buoy 3	41 25 14 N 71 30 07 W				Green can.	Private aid.
							3/04
*19679	Billington Cove Marina Channel Buoy 4	41 25 14 N 71 30 06 W				Red nun.	Private aid.
							3/04
*19680	Billington Cove Marina Channel Buoy 5	41 25 19 N 71 30 10 W				Green can.	Private aid.
							3/04
29135	<i>- Channel Lighted Buoy 6</i>	40 37 46 N 73 19 08 W	Q R		3	Red.	Replaced by nun when endangered by ice.
	*						3/04
29155	<i>- Channel Lighted Buoy 7</i>		FI G 4s		4	Green.	Replaced by can when endangered by ice.
							*
							3/04
29195	<i>- Lighted Buoy 18</i>		FI R 4s		3	Red.	Replaced by can when endangered by ice.
							*
							3/04
30770	<i>- Lighted Buoy 17</i>		FI G 2.5s		4	Green.	Replaced by can when endangered by ice.
							*
							3/04
30875	<i>- Lighted Buoy 34</i>		Q R		3	Red.	Replaced by can when endangered by ice.
							*
							3/04

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
155	Cape May Light	38 55 59 N 74 57 37 W	FI W 15s	165	24	White tower, red cupola, two white dwellings nearby.	
						*	3/04

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME II LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
942	- NORTH BREAKWATER LIGHT 6	39 45 33 N 74 05 23 W	Q R	40	5	TR on multi-pile structure.	
						*	3/04
16205	MILL CREEK ENTRANCE LIGHT 2MC	37 47 37 N 76 17 47 W	FIR 4s	15	4	TR on pile	
		*			*		3/04
16255	COCKRELL CREEK LIGHT 1	37 49 10 N 76 17 04 W	FI G 4s	15	4	SG on pile.	
		*					3/04
21405	Latimer Shoal Junction Buoy LS	37 05 49 N 75 59 32 W				Red and green bands; nun.	
		*					3/04
35155	- LIGHT 42	39 45 47 N 74 10 14 W	Q R	17	3	TR-TY on multi-pile structure.	Maintained year round.
		*					3/04
35210	- LIGHT 57	39 41 07 N 74 09 49 W	FI G 2.5s	15	3	SG-SY on pile.	
					*		3/04
35360	- LIGHT 92	39 35 47 N 74 13 35 W	FIR 4s	15	4	TR-TY on pile.	
		*			*		3/04

CORRECTIONS TO C. G. LIGHT LIST, VOLUME III LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
245	<i>Kiawah Island Lighted Whistle Buoy 4KI</i>						<i>Remove from list.</i>
							*
							3/04
6600	- <i>Lighted Buoy 16</i>		FIR 2.5s		3	Red.	
	*						3/04
6605	- <i>Lighted Buoy 17</i>		FI G 2.5s		3	Green.	
	*						3/04
19910	- <i>Channel Lighted Buoy 3</i>		Q G		3	Green.	
	*						3/04

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
9603	Fritchie March Weir Danger Daybeacons (4)	30 13 45 N 88 44 48 W		7		NW on pile worded DANGER DO NOT PROCEED.	Marks weir. Private aid.
		*					3/04
23260	- INNER RANGE REAR LIGHT 1200 yards, 268.9° from front light.		Oc G 4s	71		KRW on pile.	Visible only on the channel line.
	*			*			* 3/04
23555	- Lighted Buoy 94						Remove from list.
							* 3/04
*23556	- LIGHT 94 150 feet outside the channel limit.	29 41 23 N 94 59 06 W	FI R 4s	17	4	TR on pile.	Ra ref.
							3/04
*23562	- LIGHT 96 120 feet outside the channel limit.	29 41 39 N 94 59 25 W	FI R 6s	17	4	TR on pile.	Ra ref.
							3/04
23995	- LIGHT 107 130 feet outside the channel limit.		FI G 6s	17	5	SG on pile.	Ra ref.
	*						3/04
24000	- LIGHT 108 130 feet outside the channel limit.	29 42 52 N 95 01 10 W	FI R 6s	17	4	TR on pile.	
	*	*					3/04
24025	- LIGHT 109 100 feet outside the channel limit.	29 43 13 N 95 01 19 W	FI G 4s	17	5	SG on pile.	Ra ref.
	*	*					3/04
*24026	- LIGHT 110 215 feet outside the channel limit.	29 43 12 N 95 01 09 W	FI R 4s	17	4	TR on pile.	Ra ref.
							3/04
24030	- Buoy 110A					Red nun.	
	*						3/04
24100	- Buoy 112A						Remove from list.
							* 3/04
*24100.05	- LIGHT 112A 125 feet outside the channel limit.	29 43 53 N 95 01 56 W	FI R 2.5s	17	4	TR on pile.	Ra ref.
							3/04
24105	- Lighted Buoy 114						Remove from list.
							* 3/04

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME IV LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
*24105.05	- LIGHT 114 120 feet outside the channel limit.	29 43 56 N 95 02 16 W	FI R 4s	17	4	TR on pile.	Ra ref. 3/04
*24106	- LIGHT 114A 120 feet outside the channel limit.	29 43 56 N 95 02 27 W	FI R 6s	17	4	TR on pile.	Ra ref. 3/04
*24108	- LIGHT 114B 240 feet outside the channel limit.	29 43 57 N 95 02 38 W	FI R 4s	17	4	TR on pile.	Ra ref. 3/04

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
236	NOAA Environmental Lighted Buoy EB 46063	34 16 20 N 120 39 52 W	FI (4) Y 20s			Yellow disc-shaped buoy.	 3/04
		*					
325	NOAA Environmental Lighted Buoy 46012	34 26 58 N 122 41 44 W	FI (4) Y 20s			Yellow disc-shaped buoy.	 3/04
		*					
510	NOAA Environmental Lighted Buoy EB 46006	40 49 50 N 137 29 11 W	FI (4) Y 20s			Yellow boat-shaped buoy.	 3/04
		*					
2445	- EAST JETTY LIGHT 4	33 35 23 N 117 52 39 W	FI R 4s	25	6	TR on pile.	 3/04
		*					
2450	- CHANNEL LIGHT 5	33 35 56 N 117 52 58 W	FI G 2.5s	12	5	SG on pile.	 3/04
		*					
2455	- CHANNEL LIGHT 6	33 35 56 N 117 52 51 W	FI R 4s	18	4	TR on pile.	 3/04
		*					
2780	- RANGE FRONT LIGHT	33 44 13 N 118 05 32 W	Q G	45		KRW on skeleton tower.	Visible 4° each side of rangeline. Light operates continuously. 3/04
		*					
3020	- Lighted Buoy 3	33 43 36 N 118 11 33 W	FI G 4s		4	Green.	 3/04
		*					

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003							
(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
4900	- LIGHT 10	37 41 12 N 122 12 07 W	FI R 4s	15	3	TR on pile.	Ra ref.
		*					3/04
4905	- LIGHT 12	37 41 28 N 122 11 47 W	FI R 6s	15	3	TR on pile.	Ra ref.
		*					3/04
SAN FRANCISCO BAY - SOUTHERN PART (Chart 18651)							
San Bruno Shoal							
4945	- CHANNEL LIGHT 1	37 41 45 N 122 20 22 W	FI G 4s	15	4	SG on pile.	HORN: 1 blast ev 30s (3s bl). Operates continuously from Oct. 1 to Apr. 1. Ra ref.
		*					3/04
4965	- CHANNEL LIGHT 5	37 38 39 N 122 18 48 W	FI G 4s	15	3	SG on pile.	HORN: 1 blast ev 10s (1s bl). Operates continuously from Oct. 1 to Apr. 1. Ra ref.
		*					3/04
9605	- SOUTH JETTY LIGHT 4	44 36 34 N 124 04 46 W	FI R 2.5s	20	3	Red pile structure.	Due to heavy weather conditions, the dayboards have been permanently removed from this aid. HORN: 1 blast ev 15s (2s bl). Operates continuously. Light and fog signal maintained from May 20 to Oct. 1.
							* 3/04
*10719	WILLOW GROVE DEFLECTION BOOM LIGHT	46 10 23 N 124 05 03 W	FI W 4s	20		NW on pile worded DANGER LOG BOOM.	Private aid.
							3/04
22328	Behm Canal Range Rear Daybeacon 1,600 yards, 212° from front light.	55 31 31 N 131 50 28 W		60		KRW on skeleton tower.	
	*	*					3/04
23605	GAMBIER BAY ENTRANCE LIGHT 2	57 27 54 N 133 55 13 W	FI R 6s	16	4	TR on skeleton tower.	
		*					3/04
23610	WINDHAM BAY ENTRANCE LIGHT	57 33 42 N 133 32 36 W	FI W 6s	35	6	NR on small house.	
		*					3/04
23650	GRAND ISLAND LIGHT	58 05 58 N 134 06 28 W	FI W 6s	47	6	NR on skeleton tower.	Obscured from 335° to 116°.
		*					3/04

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.

SECTION II

CORRECTIONS TO C. G. LIGHT LIST, VOLUME VI LIGHT LIST, 2003

(1) No.	(2) Name and Location	(3) Position	(4) Characteristic	(5) Height	(6) Range	(7) Structure	(8) Remarks
Copper River Delta							
<i>CAUTION: Only mariners with a thorough local knowledge of area should attempt passage into the Delta unless during emergency situations.</i>							
25455	SOFTUK BAR CHANNEL LIGHT S	60 13 38 N 144 58 18 W	Oc W 4s	12	6	NR on skeleton tower.	Maintained from May 1 to Oct. 1.
		*					3/04
Womens Bay							
26765	- FRONT RANGE LIGHT	57 43 24 N 152 28 51 W	Q W	43	4	KRB on skeleton tower.	
					*		3/04
26770	- REAR RANGE LIGHT 630 yards, 211.1° from front light.	57 43 07 N 152 29 10 W	Oc W 4s	90	4	KRB on skeleton tower.	
					*		3/04
27832	St. Paul Outfall Range Daybeacons (2)						<i>Remove from list.</i>
							*
							3/04
27840	- Buoy 3	59 32 09 N 162 16 48 W				Green can.	
		*					3/04
27851	- Buoy 6	59 43 32 N 162 17 56 W				Red nun.	
		*					3/04
27855	- Buoy 12	59 53 42 N 162 15 22 W				Red nun.	
		*					3/04
27965	- WEST JETTY LIGHT	64 29 49 N 165 24 55 W	FI G 4s	15	4	On post.	Maintained from July 1 to Nov. 1.
					*		3/04

Note: Asterisks (*) indicate that column(s) in which a correction has been made or new information added.
Denotes a new entry when preceding the station number.